

















Type	n°	n°	n°
<b>AGRITECH 2000</b>	10	16	4



**KIT Optional**

Art. 1220

													
Type	lt.	Model	l/min	m <sup>3</sup> /h	r.p.m.	hp	r.p.m.	n°	stage n°	bar	p.s.i.	kg	L x B x H
<b>AGRITECH 2000</b>	25+50	K 60	2035	122	1400	50	250/325	4	2	11	160	250	1150 780 1100

### Compressori portati attacco tre punti trattore

Sono caratterizzati da testate super professionali con cilindro e piatto valvole in ghisa, per un elevato rendimento ed una lunga durata. Il telaio compatto e robusto è dotato di gruppo filtro-riduttore-lubrificatore, manometri in bagno di glicerina e rubinetti rapidi multipli per il lavoro contemporaneo fino a 6 operatori.

La completezza della gamma da 540 a 2000 litri al minuto di aria aspirata rende i modelli della gamma Agritech adatti sia alla piccola che alla grande azienda. Tutti i modelli della serie Agritech sono predisposti per essere carrellati.

### Compressors suitable to be attached to the three points of the tractor

Their super professional heads with cylinder and valve plate in cast iron assure a high performance and a long lasting work. The compact and solid frame is equipped with a filter-reducer-lubricator group, glycerine-bath pressure gauges and multiple rapid cocks which allows up to 6 operators working at the same time.

All models of the line Agritech are suitable for both small and large farms thanks to their complete range from 540 to 2000 lt./min. of air displacement. All models of the line Agritech can be provided with wheels.